



PRODUCT DATA SHEET
FX-100™

FIRE RETARDANT COATING

FLAME SEAL PRODUCTS, INC.

15200 West Drive
Houston, TX 77053 USA

713-668-4291 (office)
713-668-1724 (fax)

FX-100 is a proprietary resin designed specifically as an Intumescent Safety Coating. FX-100 is mainly designed for interior applications, but can be used in some exterior applications with a water proof top coat. The product can be applied over most surfaces to form a protective fire retardant layer. When the coating is exposed to fire or extreme heat, a thick, protective layer of foam and carbon char develops, isolating the substrate from the fire.

APPLICATION

FX-100 is not waterproof or UV resistant. If the product is applied on exterior surfaces or high humidity interior applications, a water proof top coat must be applied to ensure the long-term protection of the system.

Properly applied FX-100 provides Class A or Class B protection. FX-100's Class A rating was achieved at 7.64 wet mils on Douglas Fir. A slightly modified version passed the U.L. V 94.0 test on PVC.

The product may be used on most surface types as long as the product adheres to the substrate. It is recommended that a small sample be tested for adhesion prior to full-scale application.

Flame Seal Products also has a non-flammable primer/tie coat (ADH-1) available for helping FX-100 stick to hard-to-adhere-to surfaces, such as plastics.

PACKAGING AND HANDLING

FX-100 is a two-part product sold as a single unit to allow for easy use. When you order 1 gallon of FX-100 you will receive the proper amount of FX-100 resin and T50 curing agent to make up 1 gallon of finished product.

MADE IN THE U.S.A.

™ US Trademark of Flame Seal Products, Inc.
Registered in the US Patent & Trademark Office.

Rev. 04/15/2015



PRODUCT DATA SHEET
FX-100™

FIRE RETARDANT COATING

FLAME SEAL PRODUCTS, INC.

15200 West Drive
Houston, TX 77053 USA

713-668-4291 (office)
713-668-1724 (fax)

PACKAGING CONFIGURATION:

- 1 gallon kit: one gallon bottle containing 0.8 gallons FX-100 resin and one quart bottle containing 0.2 gallons T50.
- 5 gallon kit: five gallon bottle containing 4 gallons of resin and one gallon bottle containing 1 gallon of T50.
- 55 gallon kit: 55 gallon drum containing 44 gallons of resin and one bottle containing 11 gallons of T50.
- Refer to MSDS for proper handling.

STORAGE CONDITIONS

Temperature Range - 40°F to 90°F.

SHELF LIFE

One year from date of manufacture.

WARRANTIES

Products are guaranteed to perform their fire retardant function as represented by third party tests, if applied according to manufacturer’s published instructions. Products may not be diluted or altered prior to use.

TYPICAL ANALYSIS

Total Solids	63 – 67%
Weight per Gallon	11.1 – 11.5 lbs
Specific Gravity	1.34 – 1.39
pH	2.5 – 3.5

Product contains no PBDE’s (Polybrominated Diphenyl Ethers) or petroleum derivatives.

MADE IN THE U.S.A.

™ US Trademark of Flame Seal Products, Inc.
Registered in the US Patent & Trademark Office.

Rev. 04/15/2015

*There are no other warranties either expressed or implied since Flame Seal Products, Inc. cannot control the actual application of the products. Users must determine usability and suitability for their particular requirements, as well as compatibility with the exact materials to be treated or coated.